


30 & 80-Gallon or Base-Mount | Two Stage Gasoline

This two stage air compressor provides the high capacity air flow required for most commercial, industrial, automotive and service body applications.



Compressor Pump

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Engine

- Electric start standard - battery and cables not included

Frame

- Powder coated ASME coded 30 or 80-gallon receiver tank (Tank-mounted models only)
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Removable base plate offers flexible installation


Components

- Regulator and two gauges for tank and outlet pressure
- ASME safety valves
- 16 1/2-inch fly wheel
- Tank drain valve
- Service truck mount kit (Standard on base-mount models only)

ABS-14S-30H



30-Gallon Models



80-Gallon Models

Tank-Mounted Models	CFM @ PSI*	Displacement/Engine	Compressor	Tank Size	Engine Idle Control	Dimensions (LxWxH)	Ship Wt.	Net Wt.
ABS-13H-30H	29.0 @ 175	389cc Honda GX390 OHV	Two stage, cast iron	30-gallon	Pneumatic	38x23x46in.	480 lb.	416 lb.
ABS-14K-30H	29.0 @ 175	429cc Kohler CH440 OHV	Two stage, cast iron	30-gallon	Cable throttle	38x23x46in.	480 lb.	416 lb.
ABS-14S-30H	29.0 @ 175	404cc Subaru EX40 OHC	Two stage, cast iron	30-gallon	Cable throttle	38x23x46in.	480 lb.	416 lb.
ABS-13H-80H	29.0 @ 175	389cc Honda GX390 OHV	Two stage, cast iron	80-gallon	Pneumatic	52x26.5x53in.	560 lb.	496 lb.
ABS-14S-80H	29.0 @ 175	404cc Subaru EX40 OHC	Two stage, cast iron	80-gallon	Cable throttle	52x26.5x53in.	560 lb.	496 lb.

Base-Mounted Models	CFM @ PSI*	Displacement/Engine	Compressor	Tank Size	Engine Idle Control	Dimensions (LxWxH)	Ship Wt.	Net Wt.
ABS-13H-B	29.0 @ 175	389cc Honda GX390 OHV	Two stage, cast iron	Base-mount	Pneumatic	36.5x19x28in.	279 lb.	215 lb.
ABS-14S-B	29.0 @ 175	404cc Subaru EX40 OHC	Two stage, cast iron	Base-mount	Cable throttle	36.5x19x28in.	279 lb.	215 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

Part Number	Description	Fits Models
AW-6000-1002	Equipment cover - Keeps your equipment clean, dry and looking like new	30-gallon & base-mount models
AX-0077	Battery box and tray - Attaches to engine side of unit	30 & 80-gallon models
IX-0001	Vibration isolator pads - Isolators protect the unit from vibration during use; recommended for models that are mounted in service truck applications	30 & 80-gallon models
IX-0055	Remote start/choke - 6-ft. wire extension for key switch	Honda models