

DEALER HOT WATER PRESSURE WASHERS

Portable Gasoline

Direct/Belt Drive | DHG Series

McHenry
PRESSURE CLEANING SYSTEMS

The new 12V hot water gas pressure washer series may be compact but it is capable of cleaning the toughest grime. Completely portable, this 4000 PSI unit features a 12V Beckett burner with a 4-pancake bottom-fired heat exchanger.



DHG-4004-D0H6G
Direct Drive

Pump

- Direct or belt drive triplex piston General pump with ceramic plungers
- Stainless-steel and brass unloader valve, adjustable
- Forged brass manifold
- Thermal relief valve

Engine

- Performance proven engine with low-oil protection
- 12V electric start (battery not included)

Frame

- Reinforced powder coated steel tube frame with center balanced lifting hook
- 15-inch pneumatic tires

Components

- 1/2-inch schedule 80 pipe coil with 4-pancake bottom-fired heat exchanger
- 12V Beckett burner
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)
- Adjustable thermostat
- Hour meter
- 250°F steam

Miscellaneous

- Temperature rise 130°F/54°C above ambient, maximum outlet temperature is 210°F
- Water output temperature is 250°F in "wet" steam

Unit Includes:

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 1/4-inch MEG and 1/4-inch MQC wet steam nozzle – 25°
- 50-foot x 3/8-inch steel wire-braided high pressure hose with quick connects, swivel and bend restrictors
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off

DHG-4004-B0H6G
Belt Drive shown with
stainless-steel coil wrap
option, HX-0273



Made in
USA
with Globally Sourced
Components

Exclusive
Dealer
Product

SP
C US
CSA
CERTIFIED

DEALER HOT WATER PRESSURE WASHERS

Portable Gasoline

Direct/Belt Drive | DHG Series



Direct Drive

Model Number	PSI	GPM	Displacement/Engine	Pump	Gas Tank Capacity	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DHG-4004-DOH6G	4000	3.7	389cc Honda GX390 OHV	General	1.61 gallons	10.0 gallons	2.14 gph	299,600	57.5x35.5x59.5in.	601 lb.	478 lb.

Belt Drive

Model Number	PSI	GPM	Displacement/Engine	Pump	Gas Tank Capacity	Burner Fuel Tank Capacity	Burner Fuel Consumption	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
DHG-4004-BOH6G	4000	3.7	389cc Honda GX390 OHV	General	1.61 gallons	10.0 gallons	2.14 gph	299,600	57.5x35.5x59.5in.	643 lb.	520 lb.

Options:

Part Number	Description	Fits Models
HX-0171	Skid feet - Stationary applications	All models
HX-0273	Stainless-steel coil wrap - Converts powder coated coil wrap to a stainless-steel coil wrap	All models

Accessories:

Part Number	Description	Fits Models
50-0195	Hose reel - 13-inch, 150-foot maximum hose length	All models
50-0196	Hose reel - 16-inch, 200-foot maximum hose length	All models
AW-8400-0021	Low pressure detergent injector - Allows the user to apply the recommended detergents	All models

POWERED by **HONDA**™