

# DEALER HOT WATER PRESSURE WASHERS

## Stationary Oil-Fired

### Belt Drive | HEO Series

**McHenry**  
PRESSURE CLEANING SYSTEMS

If you are looking for a wash bay system this is the equipment for you. This efficient hot water pressure washer is set up as a stationary unit with removable side panels for easy maintenance.



#### Pump

- Belt drive triplex piston General pump with ceramic plungers
- Thermal relief valve
- Adjustable high pressure detergent injector

#### Motor

- Open drip-proof electric motor with manual thermal overload protection

#### Frame

- Powder coated steel frame and removable side panels

#### Components

- 1/2-inch schedule 80-coil with 5-pancake heat exchanger
- 10-inch draft diverter
- On/Off burner, pump and motor switches
- Pressure switch and over-pressure safety controls
- 24V control system
- Polyethylene float tank (4-gallon with in-line screen filter)
- Adjustable thermostat

#### Miscellaneous

- Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F (250°F/121°C outlet temperature with steam option)
- Designed to run off an existing fuel tank (Optional fuel tanks available)

#### Unit Includes:

- Quick connect nozzles - 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch steel wire-braided high pressure hose
- Adjustable pressure insulated dual lance with fixed detergent nozzle
- Professional-grade insulated trigger gun with safety lock-off

HEO-3004-0E3G shown with fuel tanks option, HX-0218



HEO-3004-0E3G shown with panels off

**Made in USA**  
With Globally Sourced Components

**Exclusive Dealer Product**

**CSA CERTIFIED**

# DEALER HOT WATER PRESSURE WASHERS

## Stationary Oil-Fired

### Belt Drive | HEO Series



Model Number	PSI	GPM	Horsepower/Motor	BTU per hour	Dimensions (LxWxH)	Ship Wt.	Net Wt.
HEO-2004-0E2G	2000	4.2	6.0 HP, 230V, 1Ø, 27.1A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
HEO-2004-0E3G	2000	4.2	6.0 HP, 230V, 3Ø, 17.6A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
HEO-2004-0E4G	2000	4.2	6.0 HP, 460V, 3Ø, 8.8A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
HEO-2004-0E8G	2000	4.2	6.0 HP, 208V, 1Ø, 29.8A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
HEO-2004-0E9G	2000	4.2	6.0 HP, 208V, 3Ø, 20.1A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
HEO-3004-0E2G	3000	3.9	8.0 HP, 230V, 1Ø, 38.6A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
HEO-3004-0E3G	3000	3.9	8.0 HP, 230V, 3Ø, 21.6A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
HEO-3004-0E4G	3000	3.9	8.0 HP, 460V, 3Ø, 10.8A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
HEO-3004-0E8G	3000	3.9	8.0 HP, 208V, 1Ø, 42.1A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
HEO-3004-0E9G	3000	3.9	8.0 HP, 208V, 3Ø, 24.6A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
HEO-3005-0E2G	3000	4.8	10.0 HP, 230V, 1Ø, 45.6A	428,400	56.5x29x49.75in.	878 lb.	758 lb.
HEO-3005-0E3G	3000	4.8	10.0 HP, 230V, 3Ø, 26.6A	428,400	56.5x29x49.75in.	878 lb.	758 lb.
HEO-3005-0E4G	3000	4.8	10.0 HP, 460V, 3Ø, 13.3A	428,400	56.5x29x49.75in.	878 lb.	758 lb.
HEO-3005-0E8G	3000	4.8	10.0 HP, 208V, 1Ø, 50.3A	428,400	56.5x29x49.75in.	878 lb.	758 lb.
HEO-3005-0E9G	3000	4.8	10.0 HP, 208V, 3Ø, 30.6A	428,400	56.5x29x49.75in.	878 lb.	758 lb.

Options:		
Part Number	Description	Fits Models
HX-0104	<b>K7 unloader; flow activated (Auto start/stop N/A)</b> - Converts pressure trapping unloader system to flow actuated K7 unloader	HEO-3004 models
HX-0106	<b>Hour meter</b> - Displays the number of hours unit has been in operation	All models
HX-0107 *	<b>Time delay shutdown</b> - Timer will shut off automatically when trigger gun is released and timer reaches setting	All models
HX-0108 *	<b>(1) Remote station (Auto start/stop N/A)</b> - Adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
HX-0110	<b>Additional remotes (Up to 3)</b> - Additional remotes that may be added to the unit after the first remote is installed	All models
HX-0111	<b>Auto start/stop</b> - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart	All models
HX-0112	<b>K7 unloader; flow activated (Auto start/stop N/A)</b> - Converts pressure trapping unloader system to flow actuated K7 unloader	HEO-2004 & HEO-3005 models
HX-0114	<b>Dual gun</b> - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure	HEO-3005 models
HX-0115	<b>Stainless-steel access panels</b> - Converts powder coated painted access panels to stainless-steel material	All models
HX-0116	<b>Stainless-steel coil wrap</b> - Converts powder coated painted coil wrap to stainless-steel material	All models
HX-0117	<b>Painted box kit</b> - Adds painted side and end panels	All models
HX-0118	<b>Painted and stainless-steel box kit</b> - Adds stainless-steel side panels and painted end panels	All models
HX-0120	<b>250°F steam</b> - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure	HEO-2004 models
HX-0121	<b>250°F steam</b> - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure	HEO-3004 models
HX-0122	<b>250°F steam</b> - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure	HEO-3005 models
HX-0124	<b>Auto start/stop and first remote</b> - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart; adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
HX-0216	<b>Elevated float tank, 4.0 GPM</b> - Float tank is located at the back of the unit	HEO-2004 & HEO-3004 models
HX-0217	<b>Elevated float tank, 5.0 GPM</b> - Float tank is located at the back of the unit	HEO-3005 models
HX-0218 ^	<b>(2) 10-gallon fuel tanks</b> - Adds 20-gallon fuel capacity to unit versus hose hook-up to fuel supply	All models
HX-0223 *	<b>Time delay shutdown and first remote</b> - Timer will shut off automatically when trigger gun is released and timer reaches setting; adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models

\*You cannot order HX-0107 and HX-0108 together, you will need to order HX-0223 instead. See photo of HX-0108 below.

^You must also order option HX-0216 or HX-0217 when ordering HX-0218.

